
Jata sheet Extractor hood










DH 520 white



DH 540 silver

Technical specifications		Technical specifications	
Annual energy consumption Energy efficiency class Fluid dynamic efficiency class: Lighting efficiency class: Grease filter efficiency: Exhaust performance in accordance with EN 61591 (valid as of 01.01.2015) max. noise level Operating voltage Engine	59,4 kW/h D G C 125 m ³ /h 62 dBA 230 V - 50 Hz 1 x 100 W	Annual energy consumption Energy efficiency class: Fluid dynamic efficiency class: Lighting efficiency class:: Grease filter efficiency:: Exhaust performance in accordance with EN 61591 (valid as of 01.01.2015) max. noise level Operating voltage Engine	59,4 kW/h D G C 125 m³/h 62 dBA 230 V - 50 Hz 1 x 100 W
Max. exhaust performance measured at engine Pipe connection	190 m³/h 125 mm	Max. exhaust performance measured at engine Pipe connection	190 m³/h 125 mm
Equipment Slide switch Speed levels Max. lighting	3 1 x 28 Watt Halogen /E14	Equipment Slide switch Speed levels Max. lighting	3 1 x 28 Watt Halogen /E14
Grease filter mat MI 152 (1 pack = 3 pcs.)	1 (Initial delivery already included)	Grease filter mat MI 152 (1 pack = 3 pcs.)	1 (Initial delivery already included)
Dimensions		Dimensions	
Device ground (HxWxD) Cardboard mass (HxWxD) weight net weight brut	76 x 50 x 47 mm 125 x 55 x 53 mm 4.05 kg 4.65 kg	Device ground (HxWxD) Cardboard mass (HxWxD) weight net weight brut	76 x 50 x 47 mm 125 x 55 x 53 mm 4.05 kg 4.65 kg

Errors and technical changes excepted. The delivery will be exclusive subject to our terms and conditions. Stand 02/2016