

Data sheet dishwasher

model TSG 705 white



Compact design
6 place settings
Electronic programme control
Inlet hose for safety system

Equipment

- LED control indicators for salt and Rinse aid low
- Cleaning temperatures 40-65°C
- 1 Spray level
- Continuous flow heater / covered heater
- Water softening device, adjustable
- Rinse aid dosing device
- Overflow safety device
- Safety door closure
- Stainless steel inner container / inner door
- Crockery basket
- Folding glass and plate holders
- Cutlery tray
- Adjustable feet for uneven floor
- 55 dBA Operating noise

6 programmes

- Intensive programme
- Normal programme
- ECO (economy programme)
- Glasses programme
- Quick dish washing programme
- Pre-rinsing (soaking)

Power consumption data	water/ energy consumption : 8 litres/ 0.63 kWh per washing cycle water/ energy consumption: 1760 litres / 139 kWh per year
electrical connection	Connection voltage: 230 Volt Connection output: 1930 Watt Fuse protection: 10 ampere
weight	22.5 kg
dimensions	(W/H/D) 550 x 440x 500 mm

model TSGE 706 stainless steel



Fully integrated design
6 place settings
Electronic programme control
Mechanical inlet hose for safety system

Equipment

- LED- control indicators for:
 - on/off
 - Programme selection
 - Starting process
 - salt and Rinse aid low
- Start delay 3/6/9/12 h 40-65°C
- Cleaning temperatures 40-70°C
- 1 Spray level
- Continuous flow heater / covered heater
- Water softening device
- Rinse aid dosing device
- Overflow safety device
- Safety door closure
- Stainless steel inner container / inner door
- silver gray crockery basket
- Folding glass and plate holders
- Cutlery tray
- 55 dBA Operating noise

6 programmes

- Intensive programme
- Normal programme
- ECO (economy programme)
- Glasses programme
- Express programme 60 Min
- Quick dish washing programme 30 Min.

Power consumption data	water/ energy consumption: 8 litres / 0.61 kWh per washing cycle water/ energy consumption: 2240 litres / 174kWh per year
electrical connection	Connection voltage: 230 Volt Connection output: 1280 Watt Fuse protection: 10 ampere
weight	27.0 kg
dimensions	(W/H/D) 590 x 475x 551 mm